



N = Number of poles  
 Dim L =  $N \times 7.62 + 1.5$   
 Dim P =  $(N - 1) \times 7.62$

	Dim L	Dim P
2-4p	±0.25	±0.20
5-7p	±0.30	±0.25
8-11p	±0.35	±0.30
12-16p	±0.40	±0.35

SIGN	DATE	DESCRIPTION	APPROVER
△		THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!	

**Material**

- Item a Terminal body: Thermoplastic ( UL94V-0 )
- Item b Terminal cover: Thermoplastic ( UL94V-0 )
- Item c Terminal screw: Steel Zinc plating "--" slot type
- Item d Clampage: Steel, Zinc plated
- Item e Clamp: Steel, Zinc plating
- Item f Solder pin: Copper, Tin plated

**Electrical**

- Voltage rating: 300VAC
- Current rating: 30A
- Wire range:
- Solid wire(AWG): 10-24
- Stranded wire(AWG): 10-24
- Torque(Lb-In): 4.3
- Screw: M3
- Wire strip length: 15-16mm
- Withstanding Voltage: 1.6KV
- Operating temperature: -40°C to +115°C
- Soldering temperature: 250°C±10°C/5 Sec
- Safety Approval:
- Critical dimension: ▽

**KH xx15 x 0 xxxx G**

- 02 2 CONTACTS
- 03 3 CONTACTS
- ... ..
- 16 16 CONTACTS

0 Black (RAL9005)  
 2 Red (RAL3001/D)  
 3 Orange(RAL2011/P)  
 4 Yellow(RAL1018/A)  
 5 Green(RAL6018/T)  
 6 Blue (RAL5015/A)  
 8 Grey(RAL7035/D)

G RoHS compliant (lead<4%)  
 In copper Alloy  
 0000 Standard @ Logo  
 000A Standard ANY Logo  
 Any special item by customer request, please contact sales department.

<b>ANYTEK</b>				<b>CUSTOMER COPY</b>			
ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD							
TITLE		KH 7.62 Series 90D Wire inlet					
PART NO.		KHxx15x0xxxxG			DWG NO.		8KH0102
APPROVED		CHECKED	DESIGNED	DRAWN	CUST NO.		Tolerance
				Chen Bo 12/30'11			X. ±0.50
					UNIT: mm SCALE: NONE		X.X ±0.30
							SHEET: 01/01
							X° ±1°