

| SIGN | DATE | DESCRIPTION | APPROVER |
|------|----------|--|----------|
| △ | 2009.1.7 | APPROVAL: cULus | Kind |
| △ | 2009.7.2 | COVER TRANSPARENT PVC TO PC | Aaron |
| △ | 11/20'12 | Change the screw plating specification | Jacky |

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

MATERIALS ELECTRICAL

RATED VOLTAGE & CURRENT: 300 V, 15 A
 WITHSTAND VOLTAGE: AC 2000 V/Min
 INSULATION RESISTANCE: 1000 MΩ OR MORE AT DC 500 V
 OPERATING TEMPERATURE RANGE: -40 °C ~ +115 °C
 SCREW TORQUE VALUE: 5.2 Lb-In.
 WIRE RANGE: 14 ~ 22 AWG
 1) MOLDED PARTS: THERMOPLASTIC, UL 94 V-0 BLACK
 2) TERMINAL: BRASS, 0.8t, Tin PLATED
 3) TERMINAL SCREWS: STEEL, M3
 4) COVER: TRANSPARENT, PC

APPROVAL: cULus

PART No.:

Critical dimension: ▽

YK 302xx 1 x x 00G

G RoHS compliant
(lead<4%) In copper Alloy

NO. OF POLES
 02: 2 POLES
 03: 3 POLES
 04: 4 POLES
 ...
 18: 18 POLES

MARK
 0: "Q" MAK
 1: "ANY" MAK

TERMINAL & SCREW PLATED


0: TERMINAL & SCREW: G/F
 △ 1: TERMINAL: G/F, SCREW: Zinc
 2: TERMINAL: Sn, SCREW: G/F
 △ 3: TERMINAL: Sn, SCREW: Zinc

| DIM | TOL | | | | |
|-------|-----------------|--------|---------|---------|-------|
| | 2P-4P | 5P-10P | 11P-16P | 17P-20P | |
| Dim A | (N+2)×7.62 | ±0.20 | ±0.30 | ±0.40 | ±0.50 |
| Dim B | (N-1)×7.62 | ±0.20 | ±0.30 | ±0.40 | ±0.50 |
| Dim C | (N-1)×7.62+9.54 | ±0.20 | ±0.30 | ±0.40 | ±0.50 |

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

| TITLE | | YK-302 With Flange & cover Series | | | |
|----------|---------------|-----------------------------------|---------------------|--|---|
| PART NO. | YK302xx1xx00G | DWG NO. | 8YK0002-302 | | |
| APPROVED | CHECKED | DESIGNED | DRAWN | CUST NO. | Tolerance |
| | | Jacky 2012.11.20 | Jacky 2012.11.20 |  UNIT: mm SCALE: NONE SHEET: 01/01 REV.: D | X. ±0.50 X.X ±0.30 X.XX ±0.10 X° ±1° |

