



SIGN	DATE	DESCRIPTION	APPROVER
△	11/3'09	Add Note and connection data.	Kind
△	06/02'11	The dimension is changed from 2.6mm to 2.4mm	Runner
△	06/02'11	The dimension is changed from 0.60±0.03mm to 0.60±0.05mm	Runner
△	06/02'11	The dimension is changed from 23.23mm to 23.4mm	Runner
△	06/02'11	The dimension is changed from 4.86mm to 4.83 <sup>+0.00</sup> <sub>-0.10</sub> mm	Runner
△	06/02'11	Add the Measuring dimension	Runner
△	01/04'13	change the dimensional tolerance	Chen Bo
△	01/04'14	Add the dimensional	Chen Bo

**THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!**

- △ Note:
- Module female contact, is inserted into the plug housing K15.08 after crimping the conductor, for conductors from 0.5 to 1.0 mm<sup>2</sup>
- Material data:
- Female contact : PhBz , Tin plated.
  - Wire guard : Stainless steel
- △ Connection data:
- Wire strip length: 4mm
  - Wire range: 0.5~1.0mm<sup>2</sup>
  - Stranded wire(AWG): 18 - 20
  - Core diameter including insulation : 1.8 mm ... 2.1 mm
  - Critical dimension: ▽

<b>ANYTEK</b>				<b>CUSTOMER COPY</b>			
ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD							
TITLE		A0 5.08 Module female contact (0.5 to 1.0 mm <sup>2</sup> )					
PART NO.		A00000100000G			DWG NO.		8A00101
APPROVED		CHECKED	DESIGNED	DRAWN	CUST NO.		Tolerance
			Chen Bo 2014.04.01	Chen Bo 2014.01.04			X. ±0.50
							UNIT: mm
					SHEET: 01/01		SCALE: 2/1
					REV.: E		X.XX ±0.10
							X° ±1°